## LIMELIGHT® COLLECTION



FreshWater® Salt System Ready



Dual Action Filtration SilentFlo Circulation



FiberCor® High-Density Insulation



Color LCD Display

# BEAM



PeopleSeatingJetsVoltage4 SeatsOpen19 Jets115 or 230 V

#### Size

6'8" x 6'8" x 33" | 203 cm x 203 cm x 84 cm

#### **Water Care**

FreshWater® Salt System Ready



### LIMELIGHT® COLLECTION

# BEAM





#### **SHELL COLORS\***



White



Gray







Sun

**CABINET COLORS\*** 







Coastal Gray

Sable Espresso

#### **COVER COLORS**







Slate

Caramel Chestnut

#### LEGENDARY MASSAGE

#### 19 Personalized-Control Jets

- 1 XL Dual Rotary jet
- 2 Standard Single Rotary jets
- 2 Standard Directional jets
- 14 Directional Precision® jets

#### **EASY WATER CARE**

Water Care System FreshWater® Salt System Ready Filtration System Dual action, 100 sq. ft., top loading

#### LEADING ENERGY EFFICIENCY

Jet Pump

Wavemaster® 7000; Two-speed, 1.65 HP Continuous Duty,

3.5 HP Breakdown Torque

Beam II

Wavemaster® 9000; Two-speed, 2.5 HP Continuous Duty,

5.2 HP Breakdown Torque

**Circulation Pump** SilentFlo 5000® for quiet, continuous filtration

Beam I Heater

Titanium No-Fault® 1,500 W / 115 V or 6000w / 230v

Beam II

Titanium No-Fault® 6,000 W / 230 V

Insulation FiberCor® Insulation; Certified to California

Energy Commission (CEC) and APSP 14 energy efficiency standards for portable spas

3.5" to 2.5" tapered, 2 lb. density foam core Cover

SIZE

**Dimensions** 6'8" x 6'8" x 33" / 203 cm x 203 cm x 84 cm

**CAPACITY** 

**Seating Capacity** 4 seats

295 gallons / 1,115 liters **Water Capacity** 

Weight 700 lbs. / 320 kg dry; 3,860 lbs. / 1,750 kg filled\*\*

#### **ADDITIONAL FEATURES**

**Smart Spa** Technology Hot Spring Spas App, Powered by the Connected Spa Kit

Entertainment

**Water Feature** Vidro® backlit ribbon waterfall

**Cover Lifters** CoverCradle®, CoverCradle II, Lift 'n Glide®, or UpRite®

Limelight Collection Step (Coastal Gray, Steps

> Espresso, and Sable), Polymer Step (Ash) Bluetooth® Wireless Sound System (Optional)

**Control System** 

IQ 2020® with LCD control panel

115 V / 20 amp, 60 Hz (Includes G.F.C.I. protected power cord)

or 230 V / 50 amp, 60 Hz

Beam II

IQ 2020® with LCD control panel

230 V / 50 amp, 60 Hz (Includes G.F.C.I. protected sub-panel)

**Lighting System** Raio® multi-color interior points of light

Exterior multi-color lighting with timer

**Cooling System** CoolZone™ (Optional)