

## HOT SPOT® COLLECTION



Frog® @ease® In-Line  
Cartridge Ready



FiberCor®  
High-Density Insulation



Exterior Lighting

# STRIDE®



*Shown with Alpine White Shell  
and Almond Cabinet.*

<b>People</b>	<b>Seating</b>	<b>Jets</b>	<b>Voltage</b>
3 Seats	Lounge	20 Jets	115 V or 230 V

### Size

7' x 5'5" x 29" | 213 cm x 165 cm x 74 cm

### Water Care

FROG® In-Line Cartridge Ready

# HOT SPOT® COLLECTION

# STRIDE®



## SHELL COLORS\*



## CABINET COLORS\*



## COVER COLORS



## LEGENDARY MASSAGE

### 20 Personalized-Control Jets

- 1 XL Directional Hydromassage jet
- 1 XL Rotary Hydromassage jet
- 3 Directional Hydromassage jets
- 1 Rotary Hydromassage jet
- 14 Directional Precision® jets

## EASY WATER CARE

**Water Care System** FROG® In-Line Cartridge Ready

**Filtration System** 30 sq. ft., top loading

## LEADING ENERGY EFFICIENCY

**Jet Pump** Wavemaster® 6200; Two-speed, 1.5 HP Continuous Duty, 3.2 HP Breakdown Torque

**Heater** No-Fault® 1,000 W / 115 V or 4,000 W / 230 V

**Insulation** FiberCor® Insulation; Certified to California Energy Commission (CEC) and APSP 14 energy efficiency standards for portable spas

**Cover** 3.5" to 2.5" tapered, 1.5 lb. density foam core

## SIZE

**Dimensions** 7' x 5'5" x 29" / 213 cm x 165 cm x 74 cm

## CAPACITY

**Seating Capacity** 3 seats

**Water Capacity** 225 gallons / 850 liters

**Weight** 570 lbs. / 260 kg dry; 2,975 lbs. / 1,350 kg filled\*\*

## ADDITIONAL FEATURES

**Smart Spa Technology** Hot Spring Spas App, Powered by the Connected Spa Kit

**Cover Lifters** CoverCradle®, CoverCradle II, Lift 'n Glide®, or UpRite®

**Steps** Hot Spot Collection Step (Almond, Havana, and Storm), Polymer Step (Ash)

**Control System** IQ 2020® with LCD control panel  
115 V / 20 amp,\*60 Hz (Includes G.F.C.I. protected power cord)  
or 115 V / 30 amp\* or 230 V / 50 amp,\* 60 Hz

**Lighting System** Interior: 6 multi-color LED points of light  
Exterior: 4 multi-color LED points of light

\*Actual colors and products may vary from print representation. See dealer to verify.

\*\*Includes water and 7 adults weighing 175 lbs. each.

★Requires a dedicated circuit supplied to the unit at all times. Electrical requirements will vary outside the U.S.

◆G.F.C.I. protected sub-panel required in 30 amp conversion or 220 V mode. Export models available in 230 V, 50 Hz, 1,000 W heater.